



Innovation et Solutions Bois



DECLARATION of PERFORMANCE

N° BAA02

1- Unique identification code of the product-type :

Spruce Cladding with Painting and Treatment

Thicknesses : 18 to 46 mm Widths : 40 to 250 mm Lengths : \geq 900mm

2- Type, batch or serial number or any other element allowing the identification of the construction product in accordance with Article 11 (4) of Regulation (EU) No 305/2011 :

See parcel number

3- Intended use or use of the construction product in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer :

Outdoor wall installation

4- Name, trade name or registered trademark and contact address of the manufacturer in accordance with Article 11 (5) of Regulation (EU) No 305/2011:

**ISB FRANCE,
11 boulevard Nominoë - 35740 PACÉ (France)**

5- If applicable, the name and contact address of the representative in accordance with Article 12 (2) of Regulation (EU) No 305/2011 :

Not applicable

6- System or systems for the assessment and verification of the constancy of performance of the construction product in accordance with Annex V of Regulation (UE) N°305/2011 :

Système 4

7- In case of the declaration of performance concerning a construction product covered by a harmonized standard :

EN 14915+A1 : 2017

8- In case of the declaration of performance concerning a construction product for which a European Technical Assessment as been issued :

Not applicable

GROUPE ISB

ISB FRANCE - 11, boulevard Nominoë - CS 34203 - 35 742 PACÉ
Cedex Tél. +33 (0)2 99 85 61 61 - Fax +33 (0)2 99 85 61 62

SAS au capital de 43.195.290 € - 323 995 357 RCS Rennes - Siret 323 995 357 00072 - Code APE 4673 A - TVA intracommunautaire FR 08 323 995 357

9- Declared performances

Essential Characteristics	Performance Declared	Harmonised Technical Specification
Density	460 kg/m ³	EN 14915+A1 : 2017
Formaldehyde Emission	E1	
Pentachlorophenol Emission	< 5 ppm	
Thermal conductivity	0,12 W/ (m.K)	
Coefficient of resistance to water vapour	66	
Reaction to fire	F	
Coefficient of sound absorption	0,1/0,3	
Natural durability	T	
Durability afforded by protection treatment	3.1	
Name of protection treatment	Axil 3000	
Penetration class	NP1	
Retention value	4.35 g/m ²	

10- The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by :

Sébastien LEVENEZ,
Managing Director ISB France

At Pacé, the 9th november 2018